

Specification of HIOS HP-10 Digital Torque Meter PART 280-HPN-10X-C1

Product Information:

- Up to 100 data measurement can be stored in memory at a time.
- Can be checks maximum, minimum and average torque measurement.
- Torque value display can be automatically reset to zero.
- Automatically recalibrated to zero value.
- First peak measurement mode (F.PEAK) gives precision measurements of torque wrenches or manual driver.
- An input tool is available to make possible transfer of measurement data to a computer.
- Comes with an AC adapter that can be used with 100 240 volts power sources. Runs on an environmentally friendly nickel-hydrogen battery.

Peak measuring range	N·m	0.015-1
	kgf • cm	0.15-10
	lbf•in	0.15-9
	Accuracy	Within ±0.5% (F.S.)
	Measuring models	TRACK, PEAK, FIRST PEAK
	External Dimensions(mm)	230 ×124 ×65.2 (H)
	Weight(g)	1.8kg
	Charging time	1.2V NiMH x 5 cells 1,000mA (within 6 hours)
	Continuous operating time on a full charge	8 hours
	Battery life	About 300 charges
	Exclusive battery charger	Input: AC 100-240V (50 / 60Hz)
		Output: DC 7.3-8V 0.5 A

ABOUT KAISERTECH

Founded in 1998, Kaisertech Ltd is situated in Eastleigh, Hampshire.

Through hard work and dedication Kaisertech has grown to be a well-recognized supplier of electronic production equipment and tools.

Specialists in: Soldering, Static Control, Vision, Industrial Furniture, Electric crew Drivers & Special Projects.

