

HP-10



Feature

Use for making torque settings on electric screwdrivers, checking torque of torque wrenches or measuring torque of various rotating units, etc.

- Measured data can be imported to a computer.
- Up to 100 data items can be stored in the memory and controlled (applicable to HP and HDP only).
- With one unit of Torque Meter, max, min and ave torque values can be measured (applicable to HP and HDP only).
- New product, HP-1 is ideal for measuring 10N·cm or smaller torque.
- Torque for both clockwise or counterclockwise can be measured.
- As a standard specification, data output and analogue output are available.
- We offer calibration and maintenance services.
- "Inspection Report" is attached to all the Torque Meters.

HP-10

Specification

Download

[Operation Manual \(pdf\)](#)

Peak measuring range

N · m

kgf · cm

lbf · in

Accuracy

Measuring models

External Dimensions(mm)

Weight(g)

Charging time

Continuous operating time on a full charge

Battery life

Exclusive battery charger

0.015-1

0.15-10

0.15-9

Within $\pm 0.5\%$ (F.S.)

TRACK, PEAK, FIRST PEAK

230 × 124 × 65.2 (H)

1.8kg

1.2V NiMH x 5 cells 1,000mA (within 6 hours)

8 hours

About 300 charges

Input : AC 100-240V (50 / 60Hz)

Output : DC 7.3-8V 0.5 A

HP-10

Standard Accessories







Drive size	H4	1/4HEX or 5HEX
Fidaptor with safety cover (1pc)	 P/N : TF4G-Z (Yellow)	 P/N : TF6SG-Z (Yellow)
Shaft with screw	-	-
Buffer spring	-	-
Others	 Exclusive battery charger 1pc P/N : TCH-MULTI ※Overseas charger plug is different in kind depending on country	
	Inspection report 1 copy	



HP-10

Fidaptor List

Classification	Standard accessories	Options		
P/N	TF4G-Z	TF6SG-Z	TF4SG-Z	TF4S-Z
Measuring range (N · m)	0.15-0.6	0.15-0.6	0.25 or smaller	0.25 or smaller
	 (Yellow)	 (Yellow)	 (Red)	 Without a safety cover (Red)
Bit type	HIOS shank H4	HEX shank (2- step shaft) Upper : 5 HEX、 Lower : 1/4HEX	HIOS shank H4	HIOS shank H4

HP Battery Charger

国別	Voltage	The battery charger	Certificated	Order Code
Japan, US, Canada, Mexico, Taiwan, Southeast Asia① (Thailand, Philippines)	AC100-240V (Multiple input type)	 A Plug		TCH-MULTI
China	AC100-240V (Multiple input type)	 A Plug (CN)		TCH-MULTI-CN
Southeast Asia② (Vietnam, Indonesia, India,	AC100-240V (Multiple input type)	 C Plug		TCH-MULTI-CE

Singapore, Malaysia, Korea)				
Europe (U.K., Ireland)	AC100-240V (Multiple input type)	 C Plug		TCH-EU

*Please ask your distributor if you want to know the plug type for the country not described in above list.

Attention

To customers who use the old models of HP/HDP Series




The exclusive battery charger for the old models of HP/HDP Series (see the photos below) should be TCH-100N,TCH-120N,TCH-230G or TCH-230B. Check your Torque Meter . Please see the battery charger list.



HP Series



HDP Series

TCH-100N	TCH-120N	TCH-230G	TCH-230B
			
AC100V	AC100V-120V	AC220V-240V	AC220V-240V
A Plug Japan	A Plug Korea, Taiwan, US, Canada	C Plug HK, Europe, China	BF Plug Singapore, UK, Australia

Series Comparison

Model

Peak mesuring range	N · m
	kgf · cm
	lbf · in

Accuracy

Measuring models

External Dimensions(mm)	External Dimensions(mm)
	Display unit
	Detector

Weight(g)	Weight(g)
	Torque display
	Detector

Detector	Bit socket
----------	------------

Detectorcord

Charging time

Continuous operating time ona full charge

Battery life

Exclusive battery charger

HP-1**HP-10****HP-100**

-
-
-
0.015-0.9
Within ±0.5% (F.S.)
TRACK, PEAK, FIRST PEAK
230 ×124 ×65.2 (H)
-
-
1.8kg
-
-
-
-
1.2V NiMH x 5 cells 1,000mA (within 6 hours)
8 hours
About 300 charges
Input : AC 100-240V (50 / 60Hz) Output : DC 7.3-8V 0.5 A

-
0.015-1
0.15-10
0.15-9
Within ±0.5% (F.S.)
TRACK, PEAK, FIRST PEAK
230 ×124 ×65.2 (H)
-
-
1.8kg
-
-
-
-
1.2V NiMH x 5 cells 1,000mA (within 6 hours)
8 hours
About 300 charges
Input : AC 100-240V (50 / 60Hz) Output : DC 7.3-8V 0.5 A

-
0.15-10
1.5-100
1.5-90
Within ±0.5% (F.S.)
TRACK, PEAK, FIRST PEAK
230 ×124 ×65.2 (H)
-
-
1.8kg
-
-
-
-
1.2V NiMH x 5 cells 1,000mA (within 6 hours)
8 hours
About 300 charges
Input : AC 100-240V (50 / 60Hz) Output : DC 7.3-8V 0.5 A

ScrewDriver**Torque Meter****Screw****Company**

Outline

Message from the President

History

Awards

Branches

Employee's dog

ISO

Support

Contact

Distributor

FAQ

Download

Discontinued Products

About this website**News****Electric Screwdriver
General Catalog**

